



XIAMETER® AFE-1520 Antifoam Emulsion

20 percent active, food-grade, silicone emulsion

FEATURES

- Water-dilutable
- Foam prevention in food and chemical processes

BENEFITS

- Economical
- Easy to use
- Effective in both hot and cold systems
- Effective in low concentrations

COMPOSITION

- Milky-white liquid
- Silicone emulsion

APPLICATIONS

- Food processing
- Chemical
- Agrichemical
- Beverage manufacturing
- Meat, poultry and seafood applications
- Chemical fermentation operations
- Waste water treatment
- Vegetable processing

TYPICAL PROPERTIES

Specification Writers: These values are not intended for use in preparing specifications. Please contact your local XIAMETER® sales representative prior to writing specifications on this product.

Test	Unit	Value
Appearance		White
Active Ingredient	%	20
Specific Gravity, at 25°C (77°F)		1.0
Viscosity at 25°C (77°F)	cp	6,000
Consistency at 25°C (77°F)		Medium
pH		4
Emulsifier Type		Non-ionic
Suitable Diluent		Cool water

DESCRIPTION

XIAMETER® AFE-1520 Antifoam Emulsion is a 20 percent-active, food grade, silicone emulsion. This antifoam is water dilutable and effective in both hot and cold systems.

FOOD REGULATION STATUS

To get the status of XIAMETER AFE-1520 Antifoam Emulsion, please always refer to the Food Additive / Food Contact – Regulatory Information sheet available on request to our customer service.

KOSHER ACCEPTANCE

Kosher certified product available. Contact your local XIAMETER representative for current compliance information.

HALAL COMPLIANCE

Please contact your local XIAMETER representative for current Halal compliance documentation.

GMO STATUS

XIAMETER AFE-1520 Antifoam Emulsion does not contain genetically modified organisms. Dow Corning does not test for genetically modified organics.

HOW TO USE

Amount Needed

XIAMETER AFE-1520 Antifoam Emulsion is effective in very low concentrations. One to ten parts of active silicone per million parts foamer are sufficient to control foaming in many systems.

Begin trials at higher levels (10 ppm active silicone), then work down to the level of foam control desired.

The following are parts per million equivalents:
3.35 fl oz in 500 gal = 10 ppm
(99.07 mL in 1892.65 L = 10 ppm)
6.65 fl oz in 1,000 gal = 10 ppm
(192.22 mL in 3785.3 L = 10 ppm)
16.7 fl oz in 2,500 gal = 10 ppm
(493.87 mL in 9463.25 L = 10 ppm)
5.0 qt in 25,000 gal = 10 ppm
(4.7315 L in 94632.5 L = 10 ppm)

Adding the Antifoam

To produce optimal foam control, it is necessary to have the antifoam completely dispersed in the foaming medium. Follow these steps to achieve complete dispersion:

1. Agitate product prior to use.
2. Predilute with 3 to 10 parts of cool water to aid in dispersion. Add the antifoam to the water with slow mixing. Prediluted material should be used immediately. If the system can provide adequate agitation to disperse the antifoam, the antifoam emulsion may be added.
3. Add the antifoam prior to the point where foaming occurs within the system, if possible.

A preservative to guard against microbial growth is included in XIAMETER AFE-1520 Antifoam Emulsion. Dilution will substantially diminish the effectiveness of the preservative. If diluted material is to be stored for more than several days, additional preservative may be required.

Contact XIAMETER brand for additional information.

PRODUCT SAFETY INFORMATION

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL, ENVIRONMENTAL, AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE ON THE XIAMETER® WEBSITE AT WWW.XIAMETER.COM.

This product will freeze at or below 0°C (32°F). If frozen, it can be thawed and used without loss of efficiency. Agitation may be required.

STORAGE AND TRANSPORT

Product should be stored between 5 and 40°C (41 and 104°F) in original, unopened containers.

The most up-to-date shelf life information can be found on the XIAMETER website in the Product Detail page under Sales Specification.

During prolonged storage there may be a slight tendency for product separation; therefore, it is recommended that XIAMETER AFE-1520 Antifoam Emulsion be gently agitated prior to use to ensure homogeneity.

XIAMETER AFE-1520 Antifoam Emulsion will freeze below 0°C (32°F). If frozen, allow to thaw at 18–29°C (64.4–84.2°F) for at least one day and agitate gently to assure homogeneity.

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow Corning's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

TO THE FULLEST EXTENT PERMITTED BY APPLICABLE LAW, DOW CORNING SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW CORNING DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.